DolPhin

DISHWASHER USER MANUAL

"Toward the best customer service"

Dolphin promises world's best customer service.



MODEL **DW-3200** Series

DW-3200i / DW-3200S / DW-3200ie / DW-3200Se

Contents

Dishwasher Features 02_03 | Notice on Operation 04_05
Prevent electrical leakage and shock 06 | Precautions 07 | Part Name 08
Display on operating 09 | Check points before operating 10
Tip for dishwashing and M/C cleaning 11 | Dimension & Specification 12_13
A/S information 14 | Trouble shooting 15





"BEST SOLUTION FOR YOUR KITCHEN"

Dishwasher Features



JET-BEAM WASH ARM

3D jet-beam spray nozzle is designed for the optimal spray angle and actualizes strong washing efficiency like waterfall shower.

Patented 30-0380197



BUILT-IN DISPENSER

Dolphin provides built-in dispenser of detergent and rinse aid for all models which is automatically controlled at each stage by MICOM.



BUILT-IN BOOSTER

Built-in booster tank provide the effective heat saving and practical space usage. And booster tank reduces operating costs by reducing heat loss.

The heat-conduction between booster and wash tank maximizes energy efficiency (for 3000 & 5000 series).



SUPER(S-TYPE) WASH ARM

The Dolphin new technology, fixed wash arm makes dishes clean from detergent residual.

The vane of full cone nozzle and the square washing zone enables water spray to eliminate the blind spot.

Patented 10-0626274



ENERGY SAVING DEVICE (Option)

E/S device recovers the waste heat from drain water by heat-conduction. It improves washing capacity by reducing the energy consumption, heating time.


Patented 10-0462171



REMOTE CONTROLLER

Remote controller is not interrupted by installed position even in corner installation. User can read operating stage and upcoming process through FND easily.

You can set each cycle by sec. and check total running number. The test mode programmed can diagnosis working status of each part on the controller.




whin Automatic Dishwasher >>

Notice on Operation

 Never wash the vessels with poisons that can be dangerous if contamintated to the dishes



- Never open the door while operating that water
- might be dangerous to get burned by hot
- Keep the door closed while operating, otherwise dangerous to get burned by hot water



- Ground the wire. Otherwise, electric shock and leakage may occur
- Do not place anything top of dishwasher that may cause machine trouble
- Do not pour the water to the machine that can cause of electrical leakage while cleaning M/C

DolPhin

Install the machine in a well-ventilated & no flammable agent




 If a gas booster ignition error occurs, contact a service center immediately. Make sure to close gas valve and check gas leakage

 Use only low forming detergent for dishwasher. High foaming soaps can interfere with good washing

Keep chemical agents away from childern



Do not get the detergent in skin, clothes and eyes when exchanging chemicals. Detergents are highly corrosive to skin, eyes and clothing.



Wear physically & chemically impervious gloves and apron while cleaning and moving machine. Otherwise, get an injury during cleaning and moving

Avoid the materials: reactive with acids and alkalis etc






Prevent electrical leakage and shock

If the machine is not grounded, please call to service center



Equip earth leakage breaker and make sure to ground the wire to avoid an electrical accident




Never ground to a gas pipe

- Never connect explosive materials



Connect the wire to metal pipe [no PVC pipe]



Connect the wire to Copper pipe

- Copper pipe should be installed with 25cm deep

| Precautions

When using the washing machine, be sure to read the precautions for minimal malfunction and accident

Winter season and storage maintenance

- Drain water completely for freezing prevention.
- Drain water completely for long-term storage
 When operate again, call service center
- During periods of non-use, turn off circuit breaker

Caution in underground water

 If hard water is supplied to the machine, it may cause part defects of heater or pump by lime scale.

Be sure to install water softener.

(The damage caused by hard water is not covered by warranty)

Important

 When gas leakage is detected, shut down the main gas and contact the local gas company or gas supplier for the service


For your safety

 Do not store gasoline and any other flammable vapors or liquids nearby the machine



otphin Automatic Dishwasher >>





Flat racks(1)

Instruction Manual

Chemical Caps



Display on operating

"Easy to use at both sides of Machine"

Available to hang on left or right hand of dishwasher



Usage of Dishwasher

- Water: watering to wash tank
- Ready : ready to operate [heating & detergent]
- Stand by : preparation for operation
- Wash: wash dishes
- Rinse: rinse dishes
- Detergent : feeding the detergent
- Rinse aid : feeding the rinse aid
- Finish



Power


ready to operate/lock the M/C Ready




otohin Automatic Dishwasher >>

Check points before operating

- 1. Place drain pipe and strainer on right place
- 2. Check booster tank drain valve closed
- 3. Check the electrity, water and gas






2. Turn on the main switch



3. Controller



4. Await for watering after closing the door

After watering and supplying chemicals, M/C get to standby



5. Wash

- A. Put the dishes into the rack
- B Put the lack into the machine
- C. Close the door. The machine will be automatically operated by door actuation system

6. Rinse the dishes and Rinse aid feeding

After finish up the wash course, automatically operate as programmed

7. Finish

Buzz for the finish and finish & stand by lamp on

Tip for dishwashing and M/C cleaning

Proper use and care of the washing M/C can extend the life of washing M/C

Tip for washing

Scrap the dishes to remove large particles of food and debris [prewash]



Arrange the dishes in the rack. Don't stack dishes one on top of another as water must have free access to all sides of every dish




• After filling a rack, open the door, slide a rack into the dishwasher and close the door

Tip for cleaning dishwasher

- 1. Cautions for dishwasher
 - The machine must be throughtly cleaned at the end of each working shift or at least daily
 - Never use steel wool to clean the dishwasher

2. Cleaning


- Turn off the power button
- Drain wash water by taking out drain pipe and strainer
- Clean off the strainer
- Clean and flush the dishwasher inside and remove a remained soil with soft cloth or brush
- Replace all removed parts and leave the machine door open to allow inside to air out and dry
- * Safety gloves must be worn when cleaning the inside/outside of the machine, as if may cause injury





orphin Automatic Dishwasher >>

| Dimension & Specification

Dimension








Specification

Item	Spec	ltem	Spec
Model	DW-3200 Series	Type	Hood TYPE
Wash Tank	40 <i>ℓ</i>	Dimension	650(W)×650(D)×1355(H)mm 650(W)×725(D)×1425(H)mm(Option
Wash Temp	60 ~ 65℃	Wash Time	40 Sec ~ 120 Sec (8 Steps)
Rinse Tank	25 <i>l</i>	Rinse Time	6 Sec ~ 13 Sec (8 Steps)
Rinse Temp	80 ~ 85℃	Detergent	Low foaming Dishwash Detergent
Max Consumption power	4.0 ~ 13.2kW		
Used Voltage	1PH 220V 50/60Hz 3PH 380V 50/60Hz	• Wash Capaciry (hour)	51~60 Racks per hour

Available models of DW-3000series

MODEL	i Type	S Type	e (Option)	Heater
	0	0	0	2.8 kW
DW-3210	0	0	0	4.0 kW
	0	0	0	8.0 kW
DW-3280	0	0	0	0,0 KVV

| Option Spec





orphin Automatic Dishwasher >>

A/S information



 Before A/S request, please check trouble shooting and follow out instruction.



 Please ask Dolphin agent for purchasing of dishwasher, accessory and chemicals

 Contact information 	0	Contact	inf	formation
---	---	---------	-----	-----------



| Trouble shooting



Before service call, check the symptoms and related causes

Symtom	Possible cause	Solution
Higher forming than usual	Do not use dishwasher detergent?	Use dishwasher detergent
	Low temperature of wash water?	Check wash water temperature
No ignition of gas booster	Closed gas valve?	Open valve
	Closed water valve?	Open valve
	Battery out for ignition?	Exchange batteries
3	Dripped water by low pressure?	Close another valve
Gas booster kept on	Take out the drain pipe?	Put it on wash tank
ON ON	Close booster tank(ball) valve?	Close booster tank(ball) valve.
• Wash defects	Debris on the nozzles of wash arm?	Remove debris
	Runout of detergent?	Refill up a detergent
Dry defects	No rinse aid?	Refill up a rinse aid
ري	Low temperature of rinse water?	Use the M/C at the proper temperature
	Debris on nozzle of rinse arm?	Remove debris
• Weak wash blade or drip	Food or debris on the filter of wash pump	Remove debris



* The specification is subject to change without notice for improvement and the color could be different from real product.

